

PRODUCT-DETAILS

# AN20

## AN20 Inlet M20



### General Information

Extended Product Type	AN20
Product ID	2TKA160025G1
EAN	6410011527573
Catalog Description	AN20 Inlet M20
Long Description	Inlet AN20 is equipped with locking device which prevents conduit disconnection. The conduit can be unfastened by twisting it. The inlet can be used both in mounting boxes and in junction boxes. Made of halogen free material (IEC/61249-2-21).

### Environmental

RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
RoHS Information	9AKK106713A4634
REACH Declaration	9AKK106713A4633

### Dimensions

Product Net Width	0.028 m
Product Net Height	0.038 m
Product Net Depth / Length	0.026 m

Product Net Weight	0.0051 kg
--------------------	-----------

## Ordering

Minimum Order Quantity	100 piece
Package Level 1 Units	box 100 piece
Package Level 1 Gross Weight	0.51 kg
E-Number (Finland)	1152757
E-Number (Sweden)	1422343

## Certificates and Declarations

Declaration of Conformity - CE	9AKK106713A4627
--------------------------------	-----------------

## Installation

Instructions and Manuals	9AKK10103A2549
--------------------------	----------------

## Popular Downloads

Data Sheet, Technical Information	9AKK10103A2549
Building Information Modeling – BIM	9AKK108468A3684

## Classifications

ETIM 8	EC002328 - Accessories/spare parts for junction boxes/cases for mounting in the wall
ETIM 9	EC002328 - Accessories/spare parts for junction boxes/cases for mounting in the wall
WEEE Category	Product Not in WEEE Scope

## Categories

Low Voltage Products and Systems → Installation Materials → Flush Mounted Boxes → Accessories for Plastic Flush Mounted Boxes → Inlets

