

PRODUCT-DETAILS

AN25

AN25 Inlet M25



General Information

Extended Product Type	AN25
Product ID	2TKA160027G1
EAN	6410011527252
Catalog Description	AN25 Inlet M25
Long Description	Inlet AN25 is equipped with locking device which prevents conduit disconnection. The conduit can be unfastened by twisting it. The inlet can be used both in mounting boxes and in junction boxes. Made of halogen free material (IEC/61249-2-21).

Environmental

RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
RoHS Information	9AKK106713A4634
REACH Declaration	9AKK106713A4633

Dimensions

Product Net Width	0.029 m
Product Net Height	0.032 m
Product Net Depth / Length	0.028 m
Product Net Weight	0.0066 kg

Ordering	
Minimum Order Quantity	100 piece
Package Level 1 Units	box 100 piece
Package Level 1 Gross Weight	0.673 kg
E-Number (Finland)	1152725
E-Number (Sweden)	1422344

Certificates and Declarations	
Declaration of Conformity - CE	9AKK106713A4627

Installation	
Instructions and Manuals	9AKK10103A2549

Popular Downloads	
Data Sheet, Technical Information	9AKK10103A2549

Classifications	
ETIM 8	EC002328 - Accessories/spare parts for junction boxes/cases for mounting in the wall
ETIM 9	EC002328 - Accessories/spare parts for junction boxes/cases for mounting in the wall
WEEE Category	Product Not in WEEE Scope

Categories	
Low Voltage Products and Systems → Installation Materials → Flush Mounted Boxes → Accessories for Plastic Flush Mounted Boxes → Inlets	

