

PRODUCT-DETAILS

# S16/50M

## 50M X S16 CONDUIT



### General Information

Extended Product Type	S16/50M
Product ID	7TCA296010R0040
EAN	5020963001277
Catalog Description	50M X S16 CONDUIT
Long Description	Inherent Low Fire Hazard Steel Conduit, 3/8 Inch, Nominal Conduit Size 16mm, Outside Diameter 16.0mm, Inside Diameter 13.0mm, Static Bend Radius 35mm, Reel Length 50 Meters, Galvanised Steel General Purpose

### Additional Information

Application	Indoors / Outdoors - Light Industrial, Buildings
Product Type	Low Fire Hazard Conduit

### Ordering

EAN	5020963001277
UPC	786210261430

### Dimensions

Product Net Depth / Length	50 m
----------------------------	------

---

## Technical

Number of Batteries	0
Material	Galvanized Steel

---

## Environmental

WEEE Category	Product Not in WEEE Scope
---------------	---------------------------

---

## Container Information

Package Level 1 Units	1 piece
Package Level 1 Height	5 in 127 mm
Package Level 1 Depth / Length	16 in 406 mm
Package Level 1 Width	16 in 406 mm

---

## Certificates and Declarations

Data Sheet, Technical Information	S16/50M
Instructions and Manuals	S16/50M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

---

## Classifications

ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

---

## Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

