

PRODUCT-DETAILS

# S32/25M

## 25M X S32 CONDUIT



### General Information

Extended Product Type	S32/25M
Product ID	7TCA296010R0118
EAN	5020963001437
Catalog Description	25M X S32 CONDUIT
Long Description	Inherent Low Fire Hazard Steel Conduit, 1 Inch, Nominal Conduit Size 32mm, Outside Diameter 32.0mm, Inside Diameter 28.1mm, Static Bend Radius 60mm, Reel Length 25 Meters, Galvanised Steel General Purpose

### Additional Information

Application	Indoors / Outdoors - Light Industrial, Buildings
Product Type	Low Fire Hazard Conduit

### Ordering

EAN	5020963001437
UPC	786210251523

### Dimensions

Product Net Depth / Length	25 m
----------------------------	------

---

## Technical

---

Number of Batteries	0
Material	Galvanized Steel

---



---

## Environmental

---

WEEE Category	Product Not in WEEE Scope
---------------	---------------------------

---



---

## Container Information

---

Package Level 1 Units	1 piece
Package Level 1 Height	12 in 305 mm
Package Level 1 Depth / Length	16 in 406 mm
Package Level 1 Width	16 in 406 mm

---



---

## Certificates and Declarations

---

Data Sheet, Technical Information	S32/25M
Instructions and Manuals	S32/25M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

---



---

## Classifications

---

ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

---



---

## Categories

---

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

