



Dimensions

Product dimensions (mm) Ø220 x 54

Product

Real power (W) 13
Real luminous flux (Lm) 933
L.O.R. (%) 0,665477889
Luminous efficiency (Lm/W) 72
Beam angle (°) 125
Life time (h) 30000 (L70/B10)
IP IP54
IK IK06
Electrical class insulation Class 2
Electrical feeding 220..240V, 50/60Hz
Colour (RAL) White(9016)
Energy efficiency class A+
Diffuser PC opal diffuser

Control gear


Control gear included Yes
Control gear Electronic Control Gear

Light source

Light source included Yes
Light source Led
Nominal power (W) 12
Nominal luminous flux (Lm) 1402
Colour temperature (K) 4000
Colour consistency (SDCM) 6
CRI 80

Photometry

Photometry



**LOTOS ELEGANCE ROUND PC LED COMPACT V2
 1200 E IP54 840**

DESCRIPTION

Decorative round plafond from the TROLL family LOTOS. luminaire to be used as general lighting of passing areas, entrances, staircases or similar areas. Luminaire designed for wall or ceiling surface installation. Body made of polycarbonate with finish in White. Luminaire has a degree of isolation vs. environment of IP54. Luminaire adds in a PC opal diffuser with a beam angle of 125°. Luminaire adds in a 12 W LED source with colour temperature of 4000K, Colour reproduction higher than 80% and a chromatic dispersion lower than 6 SMDC. Fixture has an output flux of 933 Lm, with an efficiency of 72 Lm/W and a total consumption of 13 W. The average life for the luminaire is (h) 30000 [L70/B10]. Luminaire built-in an Electronic Control Gear fed at 220-240V; 50/60 Hz.

Item code	19.3209.0020.34
Product type	Indoor Lighting
Category	Surface & Suspended Luminaires
Family	Lotos
Subfamily	Lotos
Materials	Body made of polycarbonate with finish in White.
Optical system	Luminaire adds in a PC opal diffuser with a beam angle of 125°. 125°.
Installation instructions	Luminaire designed for wall or ceiling surface installation.