



AVK SERVICE CONNECTION VALVE, DI, PN16

03/00-010

Internal thread

AVK resilient seated service connection valves are designed with built-in safety in every detail. The wedge is vulcanized with AVK's own drinking water approved EPDM rubber compound. It features an outstanding durability due to the ability of the rubber to regain its original shape, the double bonding vulcanization process and the sturdy wedge design. The triple safety stem sealing system, the high strength stem and the thorough corrosion protection safeguard the unmatched reliability.

Product description:

Service connection valve with internal thread. For drinking water and neutral liquids to max. 70°C

Standards:

- Designed according to EN 1074 part 1 & 2, Designed according to EN 1171

Test/Approvals:

- Hydraulic test according to EN 1074-1 and 2 / EN 12266
- Seat: 1.1 x PN (in bar), Body: 1.5 x PN (in bar). Operation torque test
- Approved according to ACS-France
- Belgaqua approved material
- Approved according to ÖVGW Certificate W 1.418
- Approved according to Swedish type approval 1350 certified by KIWA

Features:

- Wedge of brass CW626N vulcanized with EPDM rubber – both brass and rubber certified for use in contact with drinking water– and shaped with guides and a special rubber profile ensuring low closing torques
- Stainless steel stem with rolled threads providing high strength
- Full circle thrust collar provides fixation of the stem and low free running torques
- Triple safety stem sealing with an NBR wiper ring, a polyamide bearing with four NBR O-rings and an EPDM rubber manchette
- EPDM bonnet gasket fixed in a recess
- Countersunk and sealed stainless steel bonnet bolts encircled by the bonnet gasket
- Full bore
- Low operating torque
- Fusion bonded epoxy coating in compliance with DIN 3476 part 1 and EN 14901, GSK approved


Accessories:

Handwheel, stem cap, extension spindle, street cover and tapping saddle.



Expect... **AVR**

The designs, materials and specifications shown are subject to change without notice due to the continuous development of our product range.



Component list:

1. Stem	Stainless steel 1.4104 (430F)	7. Manchette	EPDM rubber
2. Wiper ring	NBR rubber	8. Bonnet bolt	Stainless steel A2, sealed with hotmelt
3. O-ring	NBR rubber	9. Bonnet gasket	EPDM rubber
4. Bearing	Polyamide	10. Wedge	Brass DZR CW626N with EPDM
5. Bonnet	Ductile iron GJS-500-7 (GGG-50)	11. Body	Ductile iron GJS-500-7 (GGG-50)
6. Thrust collar	Brass DZR CW602N		

Components may be substituted with equivalent or higher class materials without prior notification.

Reference nos. and dimensions:

AVK ref. no.	DN	Dd	BSP	Product	L	H	F	F1	F2	Theoretical
	mm	mm	internal	PN Class	mm	mm	mm	mm	mm	weight/kg
03-025-00-0046499	25	25	3/4"	PN16	115	163	12	15	35	2.4
03-032-00-0046499	25	32	1"	PN16	115	163	12	15	35	2.4
03-040-00-0046499	32	40	1 1/4"	PN16	130	176	12	15	35	2.6
03-050-00-001	40	50	1 1/2"	PN16	150	203	12	15	35	4.7
03-063-00-001	50	63	2"	PN16	178	213	12	15	35	6.4