

ENSTO

Saunavalgusti

AVH11.2



Tüüp	AVH11.2
GTIN	6410041171449
Nimi	Saunavalgusti Ensto 1x40/60W A60/E27 IP44, ta125 °C
Kirjeldus	Saunavalgusti männipuust restiga. Sobib kasutamiseks ka muudes ruumides, kus on vaja pidevat püsivalgustust. Korpus kuumakindlast polüestrist, kuppel klaasist.
Müüja	Ensto Finland Oy

Spetsifikatsioon

Technical information

Dimmerdatavus:	-
Materjali kuumusindeks:	650 °C
Optics:	Puukaitsetase
Sokkel:	E27
Valgusallikas (ILCOS):	IA
Valgusallikate arv ja võimsus (W):	1x40/60
Ühendamine vooluvõrku:	Lõppühendus
Ühendamine vooluvõrku:	Kruviklemm
Ühendamine vooluvõrku:	2x1,5

Tõendid

Certificates:	FI
---------------	----

Muu

Energy label:	KUTENERGIA6
ETIM Class:	EC002892
Tootja aadress:	Ensto Finland Oy, P.O. Box 77, FI-06101 Porvoo, Finland

Hinnangud

Kaitseaste:	IP44
Kaitseaste:	II

Mõõtmed

Net Weight: 2,05 kg

Omadused

Valgusallikas: 1xA60 60W/E27

ETIM

Etim

Beam angle: Open beam/diffuse

Colour housing: Other

Control gear included: True

Covering of the luminaire with thermally insulating material possible: True

Degree of protection (IP): IP44

Dimming 0-10 V: False

Dimming 1-10 V: False

Dimming DALI: False

Dimming depending on control gear: False

Dimming DMX: False

Dimming DSI: False

Dimming GPRS: False

Dimming LineSwitch: False

Dimming mains voltage modulation: False

Dimming manufacturer's proprietary system: False

Dimming phase cut-off: False

Dimming phase cut-on: False

Dimming potentiometer (integrated): False

Dimming programmable: False

Dimming RF: False

Dimming Sine Wave Reduction: False

Dimming Zigbee: False

Dimming Touch and Dim: False

Dimming with push-button: False

Fit for monitor workplace acc. EN 12464-1: False

Height/depth: 135 mm

Lamp holder: E27

Length: 250 mm

Light outlet: Direct

Light sharing: Symmetric

Luminaire with limited surface temperature sign \D": False

Material cover: Glass transparent

Material housing: Plastic

No dim function: True

Nominal voltage: ≥ 230 V

Protection class:	II
Suitable for built-in mounting:	False
Suitable for ceiling mounting:	False
Suitable for emergency lighting:	False
Suitable for light line configuration:	False
Suitable for number of lamps:	1
Suitable for surface mounting:	True
Suitable for suspended mounting:	False
Suitable for wall mounting:	True
Type of control gear:	Not required
Type of grid:	None
Width:	250 mm
With air slots:	False
With light sensor:	False
With light source:	False
With movement sensor:	False
Voltage type:	AC

Pakend

Pakendatud alusele

Ühik:	PCE
Pakendi suurus:	81
Sügavus:	1200 mm
Laius:	800 mm
Kõrgus:	990 mm

Standard pakend

Ühik:	PCE
Pakendi suurus:	1
Sügavus:	252 mm
Laius:	252 mm
Kõrgus:	137 mm
Kaal:	2,05 kg
Kogus:	8,700048 l