

ENSTO

Seadmeklemm

KE12.12

| | |
|-----------|---|
| Tüüp | KE12.12 |
| GTIN | 6418677181788 |
| Nimi | Seadmeklemm Ensto Clampo Apparatus Al transition terminal for MCB, 50 mm ² |
| Kirjeldus | Ensto Clampo Apparatus is a universal terminal series for connecting Al/Cu conductors to equipment. |
| Müüja | Ensto Finland Oy |



Spetsifikatsioon

Muu

ETIM Class: EC000897

Mõõtmed

Juhtme ristlõige: Cu 2,5-50, Al 6-50

Kaal: 0,01 kg

Net Weight: 1,17 kg

Omadused

Kruvipea suurus: 5 mm

Poldipea: Kuuskant

Pooluste arv: 1

Tõendid

Standards: EN 60947-7-1, IEC 61545

Värvid

Värv: Hall

ETIM

Etim

Colour: Grey

| | |
|---|----------------------------|
| Connectable conductor cross section fine-strand with cable end sleeve: | 2,5 ... 35 mm ² |
| Connectable conductor cross section fine-strand without cable end sleeve: | 2,5 ... 35 mm ² |
| Connectable conductor cross section multi-wired: | 2,5 ... 50 mm ² |
| Connection position: | Sideways |
| Explosion-tested version 'Ex e': | False |
| Height at lowest possible mounting height: | 29 mm |
| Inflammability class of insulation material acc. with UL94: | V2 |
| Length: | 43 mm |
| Material insulation body: | Thermoplastic |
| Mounting method: | Other |
| Number of clamp positions per level: | 1 |
| Number of levels: | 1 |
| Operation temperature: | -5 ... 80 °C |
| Rated current I _n : | 145 A |
| Type of electrical connection 1: | Screw connection |
| Type of electrical connection 2: | Other |
| Width/grid dimension: | 16,5 mm |

Pakend

Pakendatud alusele

| | |
|-----------------|---------|
| Ühik: | pcs |
| Pakendi suurus: | 9450 |
| Sügavus: | 1200 mm |
| Laius: | 800 mm |
| Kõrgus: | 1032 mm |

Standard pakend

| | |
|-----------------|------------|
| Ühik: | pcs |
| Pakendi suurus: | 90 |
| Sügavus: | 218 mm |
| Laius: | 218 mm |
| Kõrgus: | 126 mm |
| Kaal: | 105,501 kg |
| Kogus: | 5,988024 l |