Motion detector

IS 360-1 DE

EAN 4007841 032852











1000 W max (LED-ready)





2 - 2000 lux











manufacture's gy saving warranty steinel.de/garantie

Function description

Intelligent technology for installation. Infrared wall sensor IS 360-1 DE, for indoors and out, ideal for installing in projecting roofs and suspended ceilings, 360° angle of coverage, reach can be set up to 4 m, selectable time and twilight threshold, detection zone can be customised with shrouds.

Technical specifications

Type	Motion detectors
Dimensions (Ø x H)	78 x 89 mm
Mains power supply	230 – 240 V / 50 – 60 Hz
Sensor Technology	passive infrared
Application, place	Outdoors, Indoors
Installation site	ceiling
Installation	Installation
Mounting height	2,50 – 4,00 m
Reach, radial	Ø 4 m (13 m²)
Reach, tangential	Ø 8 m (50 m²)
Detection angle	360 °
Angle of aperture	90 °
Switching zones	304 switching zones
Optimum mounting height	2,5 m
Mechanical scalability	No
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Electronic scalability	No
Twilight setting TEACH	No
Twilight setting	2 – 2000 lx

Time setting	8 s - 35 Min.
Switching output 1, resistive	1000 W
Switching output 1, number of LEDs / 6 pcs. fluorescent lamps	
Capacitive load in μF	132 μF
Constant-lighting control	No
Basic light level function	No
Settings via	Potentiometers
With remote control	No
Interconnection	Yes
Type of interconnection	Master/master
IP-rating	IP54
Material	Plastic
Ambient temperature	-20 - 40 °C
Application, room	outdoors, front door, all round the building, terrace / balcony, Indoors
Colour	black
Colour, RAL	9005
Manufacturer's Warranty	3 years
Version	black
PU1, EAN	4007841032852


Motion detector

IS 360-1 DE

black EAN 4007841 032852



Detection Zone



Mögliche Montagehöhe: 2,50 m - 4,00 m

Orange: radial Schwarz: tangential

Dimension Drawing

