


## Geberit PE harutoru 45°



Näitlik pilt

### Kasutuseesmärk

- Hoonete veeärastuseks
- Krundi veeärastuseks

### Omadused

- UV-kindel

### Tehnilised andmed

Materjal

PE-HD

Tootenumber	DN	d, ø	d1, ø	arc	H	X1	X2	X3	K1	K2	K3
379.108.16.1	30 / 30	32 mm	32 mm	45 °	10.5 cm	3.5 cm	7 cm	7 cm	2 cm	2 cm	2 cm
360.109.16.1	40 / 40	40 mm	40 mm	45 °	13.5 cm	4.5 cm	9 cm	9 cm	2.5 cm	3 cm	3 cm
360.108.16.1	40 / 30	40 mm	32 mm	45 °	13.5 cm	4.5 cm	9 cm	9 cm	3 cm	3.5 cm	3.5 cm
361.109.16.1	50 / 40	50 mm	40 mm	45 °	16.5 cm	5.5 cm	11 cm	11 cm	4 cm	4.5 cm	4.5 cm
361.112.16.1	50 / 50	50 mm	50 mm	45 °	16.5 cm	5.5 cm	11 cm	11 cm	3.5 cm	2 cm	2 cm
363.112.16.1	56 / 50	56 mm	50 mm	45 °	18 cm	6 cm	12 cm	12 cm	4 cm	3 cm	3 cm
363.115.16.1	56 / 56	56 mm	56 mm	45 °	18 cm	6 cm	12 cm	12 cm	4 cm	2.5 cm	2.5 cm
364.109.16.1	60 / 40	63 mm	40 mm	45 °	19.5 cm	6.5 cm	13 cm	13 cm	4.5 cm	4.5 cm	4 cm
364.112.16.1	60 / 50	63 mm	50 mm	45 °	19.5 cm	6.5 cm	13 cm	13 cm	5 cm	3 cm	3 cm
364.115.16.1	60 / 56	63 mm	56 mm	45 °	19.5 cm	6.5 cm	13 cm	13 cm	4.5 cm	2.5 cm	2.5 cm
364.120.16.1	60 / 60	63 mm	63 mm	45 °	19.5 cm	6.5 cm	13 cm	13 cm	4 cm	2 cm	2 cm
365.109.16.1	70 / 40	75 mm	40 mm	45 °	21 cm	7 cm	14 cm	14 cm	6.5 cm	5 cm	6 cm
365.112.16.1	70 / 50	75 mm	50 mm	45 °	21 cm	7 cm	14 cm	14 cm	6 cm	3 cm	4 cm
365.115.16.1	70 / 56	75 mm	56 mm	45 °	21 cm	7 cm	14 cm	14 cm	5.5 cm	2.5 cm	3.5 cm
365.120.16.1	70 / 60	75 mm	63 mm	45 °	21 cm	7 cm	14 cm	14 cm	4.5 cm	2.5 cm	3.5 cm
365.125.16.1	70 / 70	75 mm	75 mm	45 °	21 cm	7 cm	14 cm	14 cm	4 cm	2.5 cm	2.5 cm
366.109.16.1	90 / 40	90 mm	40 mm	45 °	24 cm	8 cm	16 cm	16 cm	7.5 cm	5.5 cm	6.5 cm
366.112.16.1	90 / 50	90 mm	50 mm	45 °	24 cm	8 cm	16 cm	16 cm	8 cm	4 cm	5 cm
366.115.16.1	90 / 56	90 mm	56 mm	45 °	24 cm	8 cm	16 cm	16 cm	7.5 cm	3.5 cm	4.5 cm
366.120.16.1	90 / 60	90 mm	63 mm	45 °	24 cm	8 cm	16 cm	16 cm	7 cm	3 cm	4 cm
366.125.16.1	90 / 70	90 mm	75 mm	45 °	24 cm	8 cm	16 cm	16 cm	6.5 cm	3 cm	3.5 cm
366.130.16.1	90 / 90	90 mm	90 mm	45 °	24 cm	8 cm	16 cm	16 cm	5 cm	2 cm	2 cm
367.109.16.1	100 / 40	110 mm	40 mm	45 °	27 cm	9 cm	18 cm	18 cm	9.5 cm	6 cm	7.5 cm
367.112.16.1	100 / 50	110 mm	50 mm	45 °	27 cm	9 cm	18 cm	18 cm	9.5 cm	5 cm	5.5 cm
367.115.16.1	100 / 56	110 mm	56 mm	45 °	27 cm	9 cm	18 cm	18 cm	9 cm	4 cm	4.5 cm
367.120.16.1	100 / 60	110 mm	63 mm	45 °	27 cm	9 cm	18 cm	18 cm	8.5 cm	3.5 cm	4 cm
367.125.16.1	100 / 70	110 mm	75 mm	45 °	27 cm	9 cm	18 cm	18 cm	7.5 cm	3 cm	3.5 cm
367.130.16.1	100 / 90	110 mm	90 mm	45 °	27 cm	9 cm	18 cm	18 cm	6.5 cm	2.5 cm	3 cm
367.135.16.1	100 / 100	110 mm	110 mm	45 °	27 cm	9 cm	18 cm	18 cm	5.5 cm	2 cm	2 cm
368.120.16.1	125 / 60	125 mm	63 mm	45 °	30 cm	10 cm	20 cm	20 cm	10.5 cm	4.5 cm	6 cm
368.125.16.1	125 / 70	125 mm	75 mm	45 °	30 cm	10 cm	20 cm	20 cm	9.5 cm	4 cm	5 cm

Tootenumber	DN	d, ø	d1, ø	arc	H	X1	X2	X3	K1	K2	K3
368.130.16.1	125 / 90	125 mm	90 mm	45 °	30 cm	10 cm	20 cm	20 cm	8.5 cm	3 cm	3.5 cm
368.135.16.1	125 / 100	125 mm	110 mm	45 °	30 cm	10 cm	20 cm	20 cm	7 cm	2.5 cm	2.5 cm
368.139.16.1	125 / 125	125 mm	125 mm	45 °	30 cm	10 cm	20 cm	20 cm	6 cm	2 cm	2 cm
369.125.16.1	150 / 70	160 mm	75 mm	45 °	37.5 cm	12.5 cm	25 cm	25 cm	13.5 cm	6.5 cm	7.5 cm
369.130.16.1	150 / 90	160 mm	90 mm	45 °	37.5 cm	12.5 cm	25 cm	25 cm	12.5 cm	5.5 cm	6.5 cm
369.135.16.1	150 / 100	160 mm	110 mm	45 °	37.5 cm	12.5 cm	25 cm	25 cm	11 cm	4.5 cm	5.5 cm
369.139.16.1	150 / 125	160 mm	125 mm	45 °	37.5 cm	12.5 cm	25 cm	25 cm	10 cm	4 cm	5 cm
369.145.16.1	150 / 150	160 mm	160 mm	45 °	37.5 cm	12.5 cm	25 cm	25 cm	7.5 cm	2.5 cm	2.5 cm
370.125.16.1	200 / 70	200 mm	75 mm	45 °	54 cm	18 cm	36 cm	36 cm	8.5 cm	10 cm	2.5 cm
370.135.16.1	200 / 100	200 mm	110 mm	45 °	54 cm	18 cm	36 cm	36 cm	7.5 cm	10 cm	0 cm
370.139.16.1	200 / 125	200 mm	125 mm	45 °	54 cm	18 cm	36 cm	36 cm	5.5 cm	9 cm	0 cm
370.145.16.1	200 / 150	200 mm	160 mm	45 °	54 cm	18 cm	36 cm	36 cm	4 cm	5.5 cm	0 cm
370.146.16.1	200 / 200	200 mm	200 mm	45 °	54 cm	18 cm	36 cm	36 cm	0 cm	0 cm	0 cm
371.135.16.1	250 / 100	250 mm	110 mm	45 °	66 cm	22 cm	44 cm	44 cm	14 cm	10 cm	7.5 cm
371.139.16.1	250 / 125	250 mm	125 mm	45 °	66 cm	22 cm	44 cm	44 cm	13 cm	13 cm	6.5 cm
371.145.16.1	250 / 150	250 mm	160 mm	45 °	66 cm	22 cm	44 cm	44 cm	10.5 cm	10 cm	0 cm
371.146.16.1	250 / 200	250 mm	200 mm	45 °	66 cm	22 cm	44 cm	44 cm	7.5 cm	0 cm	1.5 cm
371.147.16.1	250 / 250	250 mm	250 mm	45 °	66 cm	22 cm	44 cm	44 cm	4 cm	0 cm	0 cm
372.135.16.1	300 / 100	315 mm	110 mm	45 °	84 cm	28 cm	56 cm	56 cm	23 cm	20 cm	16 cm
372.139.16.1	300 / 125	315 mm	125 mm	45 °	84 cm	28 cm	56 cm	56 cm	21.5 cm	20 cm	14.5 cm
372.145.16.1	300 / 150	315 mm	160 mm	45 °	84 cm	28 cm	56 cm	56 cm	19.5 cm	17.5 cm	12.5 cm
372.146.16.1	300 / 200	315 mm	200 mm	45 °	84 cm	28 cm	56 cm	56 cm	16.5 cm	5 cm	10 cm
372.147.16.1	300 / 250	315 mm	250 mm	45 °	84 cm	28 cm	56 cm	56 cm	13 cm	5.5 cm	6.5 cm
372.148.16.1	300 / 300	315 mm	315 mm	45 °	84 cm	28 cm	56 cm	56 cm	8.5 cm	2 cm	2 cm