



Pipe end peeler RSE multi

- **Rotary peeler for reliable pipe preparation prior to electrofusion**
- The adjustable basic tool is suitable for holding dimensional pipe inserts from d20 to d75 mm.
- Applicable on pipe ends and spigot ends of fittings
- Applicable for straight and coiled pipes
- Applicable for metric pipes according to EN12201 und EN1555
- Applicable on pipe material: PE100RC, PE100, PE-Xa, PP
- Operation: manual or with cordless screwdriver
- Maximum peeling length = 75mm
- Peeling blade as reversing knife with 2 cutting edges
- Scope of delivery either without or with the pipe inserts specified in the description
- Supplementary pipe inserts to be ordered separately

d (mm)	Description	Code	Weight (kg)	SDR	e (mm)	L (mm)	B (mm)	H (mm)
	Basic tool + box	799 300 350	0.58			280	95	98
	Basic tool + case	799 300 351	1.45			391	304	134
	Basic tool+case+d32+d63	799 300 352	1.88	11		391	304	134
	Basic tool+case +d32+d40+d50+d63	799 300 353	2.18	11		391	304	134
20	Insert RSE	799 300 354	0.30	7	3.0	45	20	20
20	Insert RSE	799 300 356	0.05	11	2.0	45	20	20
25	Insert RSE	799 300 355	0.10	9	3.0	45	25	25
25	Insert RSE	799 300 357	0.10	11	2.3	45	25	25
32	Insert RSE	799 300 358	0.10	11	3.0	50	30	30
40	Insert RSE	799 300 359	0.10	11	3.7	50	40	40
50	Insert RSE	799 300 360	0.20	11	4.6	60	50	50
50	Insert RSE	799 300 370	0.20	17	3.0	60	50	50
63	Insert RSE	799 300 361	0.33	11	5.8	60	60	60
63	Insert RSE	799 300 371	0.33	17	3.8	60	60	60
75	Insert RSE	799 300 362	0.47	11	6.8	60	70	70
75	Insert RSE	799 300 372	0.47	17	4.5	60	70	70
	Blade RSE	799 300 347	0.01			7	7	3
	Handle RSE	790 308 450	0.08			60	50	50

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>